CONFIDENTIAL

# LANCER EvolutionVIII



2005 Model Year

### INFORMATION BULLETIN

#### **General Export**

ASEAN Business Planning Department Asia, Latin America, Middle East & Africa Office

P-No. 04-04 Date: February 27, 2004



## Introducing the model year 2005 Mitsubishi LANCER EVOLUTION VIII

While the improvement of overall performance has always been the basis for redesigns of the Lancer Evolution, the primary focus for the 2005 Lancer Evolution VIII is the promotion of a greater sense of unity—emotional as well as functional—between driver and car. The introduction is also timed to celebrate its re-entry after a one-year hiatus into the ultimate test of all-round automotive competitiveness: the World Rally Championship (WRC).

The even more competitive Evo VIII's newly evolved driver/car oneness is realized most effectively in greatly improved handling performance resulting from reduced overall weight and increased road-holding accuracy. A new all-aluminum roof panel (a first for MMC) and aluminum impact bars for all doors save weight, which translating into a lower center of gravity and more stable, better-balanced handling, especially when powering through corners. Another first for MMC, Recaro racing-style front bucket seats ensure full-body support.

New all-wheel BILSTEIN® shock absorbers and state-of-the-art brembo® braking system, both developed with guidance from their respective factory experts, fine-tune steering response and cornering precision regardless of surface conditions.

A variety of exterior and interior options further brings drivers together with the machine of their dreams:

- 17" BBS aluminum wheels for a more powerful image
- ●Two forceful new exterior colors: Red Solid <P85> and Medium Purplish Gray Mica <A39> (this year's theme color) respond to enthusiast demands

Sold exclusively through Ralliart Inc., the Lancer Evolution VIII will be available in the competition-oriented RS model configuration, in either left- or right-hand drive. Since the Lancer Evolution VIII is geared for competition, it will neither be warranted nor homologated for general production.



Production will begin end of June 2004, with shipment to follow in July 2004.



RECARO front bucket seats (OPT K05)



MOMO 3-spoke steering wheel (OPT F07)



Aluminum roof panel



Front McPherson strut suspension, rear multi-link suspension, brembo®\* braking system/front 17" ventilated disc (4-pot) and rear 16" ventilated drum-in-disc (2-pot)



BILSTEIN® front shock absorbers (OPT AK1)



BILSTEIN® rear shock absorbers (OPT AK1)



Aluminum side impact bars



17" BBS alloy wheels (OPT B54)

3

### Model Line-up and Color Chart General Export model year 2005 LANCER Evolution VIII

#### Model Line-up

Model Code		Deina Olasa	Fastas	Tormondados
LHD	RHD	Price Class	Engine	Transmission
CT9ASNDFZL	CT9ASNDFZR	RS	1,997 cc 16-valve DOHC Intercooled Turbocharged ECI-MULTI (4G63)	5M/T (W5M51)

#### **Color Chart**

00.0	or Chart			
Model		RS		
Model Code		CT9ASNDFZL/R		
	Interior Trim Code (Basic Color)	Normal seats	RECARO seats (OPT K05)	
Exterior Color and Color Code		19X (Black)	18J (Purple)	
A31 Cool Silver Metallic <a31></a31>		0		
A39 Medium Purplish Gray Mica <a39></a39>		0		
P85 Red Solid <p85></p85>		0		
W83 White Solid <w83></w83>		0		
Seat Covering		Fabric and Vinyl (Black)	Fabric (Center: Purple, Side: Black)	
Door Trim		Formed-type (Dark Gray)	Formed-type (Dark Gray) with Cloth-insert (Purple)	
Headlining		Non-woven Fabric (Light Gray)		
Floor Carpet		Needle Punch Velour (Gray)		

O: Available Bold: New exterior colors, interior trim code and materials

### Standard and Optional Equipment General Export model year 2005 LANCER Evolution VIII

#### Standard Equipment

Standard Equipment				
DRIVETRAIN/CHASSIS	Rear			
Engine  2.0-liter 16-valve DOHC intercooled turbocharged ECI-MULTI engine (4G63)  Water spray for intercooler Titanium/aluminum turbine turbocharger Engine oil cooler (air cooler) (larger capacity than 04MY)  Transmission	Roof antenna Large-type full carbon rear spoiler Rear window defoggers Color-keyed rear bumper with integrated under-spoiler Rear fog lamp High-mount stop lamp on rear shelf Large tail pipe			
5-speed manual transmission (closed ratio type)	INTERIOR			
Suspensions	Cockpit			
Front McPherson strut suspension —Inverted-type shock absorbers —Aluminum front lower arms —Stabilizer bar Rear multi-link suspension —Aluminum rear suspension arms —Stabilizer bar Front strut tower bar Front cross-member	Blue-painted instrument panel MOMO leather-wrapped steering wheel Dual horn Driver's and front passenger's SRS front airbags Leather-wrapped gearshift knob with dark titanium-painted panel km/h speedometer (270 km/h) Tachometer Digital trip/odometer Headlamp leveling device			
Brakes	Digital quartz clock			
Front 15" ventilated disc brakes with 2-pot calipers Rear 15" ventilated disc brakes  Steering Rack-and-pinion steering Power steering Tilt-steering column	Fuel empty warning lamp Rear fog lamp indicator Seatbelt warning lamp Cigarette lighter Ashtray Heater			
Tires and wheels	Standard floor console box			
205/65R15 94H tires	Cup holders Personal pocket			
T125/70D16 high-pressure spare tire 15" steel wheels	Doors			
Others	Child-protection rear door locks			
Electronic immobilizer	Formed-type door trims Front door pockets			
Full-time 4WD Front limited-slip differential (helical type) Active center differential Rear limited-slip differential (mechanical type) Rear end cross bar	Seats Front-faced fabric seats Front seat sliding and reclining adjusters Front 3-point ELR seatbelt with pre-tensioner × 2 Front height-adjustable seatbelt anchors			
EXTERIOR	Fixed low-back rear seat			
Front	Rear 3-point ELR/ALR seatbelt × 3			
Aluminum hood with air outlet Multi-lensed halogen headlamps with clear outer lenses Amber turn signals Color-keyed front bumper with integrated grill Front bumper extension Green laminated windshield Fixed intermittent windshield wipers and washers with mist	Headlining Sunvisors (2 pcs) with driver's side ticket holder Room lamp Map lamps Day-and-night rearview mirror Front passenger's retractable assist grip (1 pc)			
function	Flooring			
Aluminum front blistered fenders Front large-type under cover with brake cooling air guide Aluminum roof	Trunk lid opener Fuel lid opener Foot rest			
Sides	Fire-retardant materials			
Aluminum side impact bars Side airdams Blacked-out door sashes Black manually controlled door mirrors Black outer door handles	Trunk room Trunk room lamp Needle punch floor mat			

#### Ontional Equipment

Optional Equipment			
<b>Option Code</b>	ltem	Remarks	
PKG: A	<ul> <li>brembo® braking system         —Front 17" ventilated disc (with 4-pot calipers)         —Rear 16" ventilated drum-in-disc (with 2-pot calipers)     </li> <li>235/45R17 high-pressure tires and T125/70D17 high-pressure spare tire</li> <li>17" × 8.0JJ ENKEI mat processed light alloy wheels</li> <li>A and G point cross bars</li> </ul>		
PKG: B	●Power windows ●Power door mirrors		
R11	Manually controlled air conditioner		
AK1	BILSTEIN® shock absorbers	Must combine AK1 and B54. Brakes will be upgraded	
B54	17" BBS alloy wheels	to brembo®. Tire size will be upgraded to 235/45R17.	
F07	MOMO 3-spoke steering wheel (small diameter)	Must combine F07 and K05.	
K05	RECARO front bucket seats		

5


#### Major Specifications


	becilicatio	115		
Model		RS		
Model code LHD/RHD		CT9ASNDFZL CT9ASNDFZR		
Drive system		Full-time 4WD		
	AND WEIGHT			
Overall length	mm	4,490		
Overall width	mm	1,770		
Overall height	mm	1,450		
Wheelbase	mm	2,625		
Track	Front mm	1,500 (1,515)*		
Rear mm		1,500 (1,515)*		
Ground clearar	nce mm	140		
Cabin length	mm	1,880		
Cabin width	mm	1,425		
Cabin height	mm	1,185		
Curb weight	kg	1,315 (1,325)*		
Seating capacit	•	5		
PERFORMANO				
Minimum turni	ng radius m	5.9		
ENGINE				
Туре		2.0-liter 16-valve DOHC intercooled with titanium/aluminum turbine turbocharger		
Total displacen	nent cc	1,997		
Bore × stroke	mm	85.0 × 88.0		
Compression r	atio	8.8:1		
Max. output (EE0	C net) kW(PS)/rpm	206 (280)/6,500		
Max. torque (EEC	net) N•m(kg-m)/rpm	383 (39.0)/3,500		
Fuel supply system		ECI-MULTI (Electronically controlled multi-point fuel injection)		
Fuel type/tank	capacity (liters)	Unleaded premium/50		
TRANSMISSIO	ON			
Туре		5-speed manual		
Gear ratio	1st	2.785		
	2nd	1.950		
	3rd	1.444		
	4th	1.096		
	5th	0.825		
	Reverse	3.416		
	Final	4.529		
STEERING				
Туре		Rack-and-pinion (power-assisted)		
SUSPENSION	S			
Front		McPherson strut with inverted-type shock absorbers; stabilizer bar and aluminum lower arms		
Rear		Multi-link with stabilizer bar; aluminum suspension arms		
BRAKES				
Front		15" ventilated discs (2-pot)		
Rear		15" ventilated discs		
TIRES AND WHEELS				
Tires (front and		205/65R15 94H		
Wheels (front and rear)		15" steel		

#### **Dimensional Views**









mm

Note: These specifications are subject to change without notice.
\*Figures in parentheses are for models equipped with optional 17" tires and wheels.

